

## 60 liter tank i Rostfritt 304



**35,000,00 SEK /st exkl moms**

**Additional information:** Mobile frame, Aisi 304; 2 electric plug-in heaters (3000 W each) for heating the heating medium in the double jacket; this heating medium must be installed on site before commissioning; control cabinet partially incomplete (see photos)

**Volumetric volume (L):** 60 L

**Pressure in tank:** ATM - atmosferic  
**Material wet parts:** SS AISI 304 (V2A)  
**Model:** vertical

**Configuration:** insulated with heat-exchanger  
**Heat exchanger:** yes  
**Insulation:** yes  
**Mobile tank:** no  
**Top type:** open

**Total discharge:** yes  
**Type HE on the bottom:** heating/cooling jacket  
**Type HE on the cylinder:** heating/cooling jacket  
**Heat exchanger:** RVS 304  
**Documents included:** no

**Technical drawing included:** no  
**Registration plate on the tank:** yes  
**Flange for agitator:** no  
**Outlet of tank:** 13  
**Agitator:** yes

**Number of revolutions:** 51  
**Power:** 0,18  
**Internal diameter tank:** 390 mm  
**Outer diameter tank:** 600 mm  
**Cylinder height:** 440 mm

**Total height of tank:** 2.030 mm

**SKU:** 484190

## Mer information

### Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: Mobile frame, Aisi 304; 2 electric plug-in heaters (3000 W each) for heating the heating medium in the double jacket; this heating medium must be installed on site before commissioning; control

Övrig information2: cabinet partially incomplete (see photos); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 60

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Rostfritt 304

### Dimensioner av tank

Cylinderhöjd: 440 mm

Invändig diameter: 390 mm

Total höjd: 2.030 mm

Ytterdiameter: 600 mm

**Omrörare**

Kraft (kW): 0,18

Varvtal: 51

**Mer**

Värmeväxlare: RVS 304

Isolerad: Ja