60 liter tank i Rostfritt 304



36 000 SEK /st exkl moms

Additional information: Mobile frame, Aisi 304; 2 electric plug-in heaters (3000 W each) for heating the heating medium in the double jacket; this heating medium must be installed on site before commissioning; control cabinet partially incomplete (see photos)
Volumetric volume (L): 60 L
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: no
Top type: open

Total discharge: yes
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: 13
Agitator: yes

Number of revolutions: 51
Power: 0,18
Internal diameter tank: 390 mm
Outer diameter tank: 600 mm
Cylinder height: 440 mm

Total height of tank: 2.030 mm

SKU: 484190

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated with heat-exchanger
Mobil tank: Nej
Övrig information: Mobile frame, Aisi 304; 2 electric plug-in heaters (3000 W each) for heating the heating medium in the double jacket; this heating medium must be installed on site before commissioning; control
Övrig information2: cabinet partially incomplete (see photos); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 60

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 440 mm
Invändig diameter: 390 mm
Total höjd: 2.030 mm
Ytterdiameter: 600 mm

Omrörare
Kraft (kW): 0,18
Varvtal: 51

Mer
Värmeväxlare: RVS 304
Isolerad: Ja