

600 liter tank i Syrafast 316



75,000,00 kr /st exkl moms

Additional information: Vessel welded in stainless steel 304 frame; 1 pump in the frame is included in the scope of delivery; brownish deposits inside the vessel; Metallic discolouration inside

Volumetric volume (L): 600 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Internal diameter tank: 790 mm

Outer diameter tank: 900 mm

Cylinder height: 1.100 mm

Total height of tank: 2.200 mm

Total outer width: 1.250 mm

Total outer length: 1.200 mm

SKU: 568403

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Vessel welded in stainless steel 304 frame; 1 pump in the frame is included in the scope of delivery; brownish deposits inside the vessel; Metallic discolouration inside

Omrörare: Nej

Övertryck: 6 Bar

Total urtappning: Nej

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 600

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.100 mm

Invändig diameter: 790 mm

Total höjd: 2.200 mm

Ytterdiameter: 900 mm

Mer

Isolerad: Ja
