600 liter tank i Syrafast 316



75 000 SEK /st exkl moms

Additional information: Vessel welded in stainless steel 304 frame; 1 pump in the frame is included in the scope of delivery; slight build-up inside the vessel (probably limescale); Metallic discolouration inside
Volumetric volume (L): 600 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 6 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: no
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Internal diameter tank: 790 mm
Outer diameter tank: 900 mm

Cylinder height: 1.100 mm
Total height of tank: 2.200 mm
Total outer width: 1.250 mm
Total outer length: 1.200 mm

SKU: 568403

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Vessel welded in stainless steel 304 frame; 1 pump in the frame is included in the scope of delivery; brownish deposits inside the vessel; Metallic discolouration inside
Omrörare: Nej
Övertryck: 6 Bar
Total urtappning: Nej
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 600

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.100 mm
Invändig diameter: 790 mm
Total höjd: 2.200 mm
Ytterdiameter: 900 mm

Mer
Isolerad: Ja