

6000 liter tank i Rostfritt 304



212 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Volumetric volume (L): 6.000 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 20 °C

Min. temperature (°C): 5 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 4 adjustable feet

Heat exchanger: RVS 304

Insulation material: Rockwool

Outer jacket (ornamental wall): RVS 304

Spray ball: RVS 304

Manway(s): RVS 304

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Tank outlet: inside Ø 50 mm

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Top: 2,50 mm

Cylinder: 3 mm

Bottom: 3 mm

Cylinder: 2

Insulation body: yes

Bottom: 2

Insulation bottom/sides: yes



Insulation thickness: 80

Internal diameter tank: 1.750 mm

Distance from outlet to ground: 1.765 mm

Outer diameter tank: 1.905 mm

Cylinder height: 2.500 mm

Feet height: 1.765 mm

Empty weight tank: 1.200

SKU: 451949

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 20 °C

Min. arbetstemperatur: 5 °C

Mobil tank: Nej

Övrig information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 6000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 50 mm

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304

Isoleringsmaterial: Rockwool

Ytterbeklädnad: RVS 304



Dimensioner av tank

Cylinderhöjd: 2.500 mm
Höjd på fötter: 1.765 mm
Invändig diameter: 1.750 mm
Mått utlopp till marken: 1.765 mm
Ytterdiameter: 1.905 mm

Omrörare

Position motor: at the top
Typ av omrörare: propeller agitator

Tjocklek på tank

Botten: 3 mm
Cylinder: 3 mm
Topp: 2,50 mm

Tjocklek på ytterbeklädnad och isolering

Isolering botten/gavlar: Ja
Isolering mantel: Ja
Isoleringsmaterial: Rockwool

Mer

Värmeväxlare: RVS 304
Cylinder OW: 2
Botten OW: 2
Isoleringstjocklek OW: 80
Isolerad: Ja
Vikt: 1.200