

6000 liter tank i Syrafast 316



88 000 SEK /st exkl moms

Additional information: Chemistry; 4 support brackets, st. st.

Volumetric volume (L): 6.000 L

Pressure in tank: vacuum

Min. pressure (Bar): 1 Bar

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 80

Agitator: yes

Number of revolutions: 35

Power: 7,50

Internal diameter tank: 2.000 mm

Cylinder height: 1.250 mm

Total height of tank: 4.450 mm

SKU: 314876

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: vacuum

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: Chemistry; 4 support brackets, st. st.; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 6000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.250 mm

Invändig diameter: 2.000 mm

Total höjd: 4.450 mm

Omrörare

Kraft (kW): 7,50

Varvtal: 35

Mer

Isolerad: Nej
