

605 liter tank i Rostfritt 304



103,000,00 kr /st exkl moms

Additional information: Stainless steel 304 frame; manhole diameter approx. 395 mm; some residues of previous content

Volumetric volume (L): 605 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 133 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 45 L

Max Overpressure: 6 Bar

Max. working temperature: 65 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: DN40 DIN 11851

Agitator: yes

Number of revolutions: 710

Power: 3

Internal diameter tank: 880 mm

Total height of tank: 2.780 mm

Total outer width: 1.320 mm

Total outer length: 1.200 mm

SKU: 576233

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 133 °C

Mobil tank: Nej

Övrig information: Stainless steel 304 frame; manhole diameter approx. 395 mm; some residues of previous content; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the

Övrig information2: agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 605

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304



Dimensioner av tank

Invändig diameter: 880 mm

Total höjd: 2.780 mm

Omrörare

Kraft (kW): 3

Varvtal: 710

Mer

Isolerad: Ja