

6100 liter tank i Syrafast 316



125 000 SEK /st exkl moms

Additional information: Chemistry; Insulation only around the cylindrical part of the tank; flanged to the outlet is a reducing fitting (reduced to an inside pipe diameter of 50 mm; fitting components made of plastic); 1 pump is included (see photos)

Volumetric volume (L): 6.100 L

Pressure in tank: ATM - atmosferic
Max. temperature (°C): 80 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: no

Total discharge: yes
Volume: 330 L
Max. working temperature: 80 °C
Type HE on the cylinder: heating/cooling jacket
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: flange DN80
Agitator: yes

Number of revolutions: 725 / 1450
Power: 3.6 / 5.3
Cylinder: 6,20 mm
Bottom: 4 mm
Internal diameter tank: 1.990 mm

Outer diameter tank: 2.170 mm
Cylinder height: 1.800 mm
Total height of tank: 3.650 mm

SKU: 299172

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 80 °C

Mobil tank: Nej

Övrig information: Chemistry; Insulation only around the cylindrical part of the tank; flanged to the outlet is a reducing fitting (reduced to an inside pipe diameter of 50 mm; fitting components made of plastic); 1

Övrig information2: pump is included (see photos); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 6100

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 1.800 mm
Invändig diameter: 1.990 mm
Total höjd: 3.650 mm
Ytterdiameter: 2.170 mm

Omrörare

Kraft (kW): 3.6 / 5.3
Varvtal: 725 / 1450

Tjocklek på tank

Botten: 4 mm
Cylinder: 6,20 mm

Mer

Isolerad: Ja