6150 liter tank i Rostfritt 304



75 000 SEK /st exkl moms

Additional information: Pure water; Manhole DN 500; 1 stainless steel reinforcement ring around the outside of the cylinder; the loose stainless steel parts also on the pallet are not included in the scope of delivery (see photos); manhole cover plated; Metallic discolouration inside
Volumetric volume (L): 6.350 L
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. temperature (°C): 90 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Position of manway: cylinder
Outlet of tank: 58
Internal diameter tank: 1.430 mm
Cylinder height: 3.500 mm
Total height of tank: 4.700 mm

SKU: 564292

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single-skin
Max. arbetstemperatur: 90 °C
Mobil tank: Nej
Övrig information: Pure water; Manhole DN 500; 1 stainless steel reinforcement ring around the outside of the cylinder; the loose stainless steel parts also on the pallet are not included in the scope of delivery (see
Övrig information2: photos); manhole cover plated;Metallic discolouration inside
Omrörare: Nej
Total urtappning: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 6350

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 3.500 mm
Invändig diameter: 1.430 mm
Total höjd: 4.700 mm

Mer
Isolerad: Nej