

## 620 liter tank i Syrafast 316



**228,000,00 SEK /st exkl moms**

**Additional information:** Pharmacy; Mobile frame, stainless steel with 4 plastic castors

**Volumetric volume (L):** 620 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 4 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 135 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 12 L

**Max Overpressure:** 4 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 135 °C

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** 40

**Agitator:** yes

**Power:** 0,75

**Top:** 6 mm

**Cylinder:** 4 mm

**Bottom:** 5 mm

**Internal diameter tank:** 800 mm

**Outer diameter tank:** 1.010 mm

**Total height of tank:** 2.050 mm

**SKU:** 483528

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 135 °C

Mobil tank: Nej

Övrig information: Pharmacy; Mobile frame, stainless steel with 4 plastic castors; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 4 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 620

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316



## Dimensioner av tank

Invändig diameter: 800 mm

Total höjd: 2.050 mm

Ytterdiameter: 1.010 mm

## Omrörare

Kraft (kW): 0,75

## Tjocklek på tank

Botten: 5 mm

Cylinder: 4 mm

Topp: 6 mm

## Mer

Isolerad: Ja