630 liter tank i Syrafast 316

32 000 SEK /st exkl moms

Additional information: The tank is mounted on a mobile frame made of Fe (painted)
Volumetric volume (L): 630 L
Pressure in tank: pressure
Max. pressure (Bar): 3,20 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)
Model: horizontal
Configuration: single-skin
Heat exchanger: no
Insulation: no

Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Outlet of tank: available

SKU: 738223

Mer information

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Beskrivning av produkt

Material: Syrafast 316
Modell: Horisontell
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: single-skin
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: The tank is mounted on a mobile frame made of Fe (painted)
Omrörare: Nej
Övertryck: 3,20 Bar
Total urtappning: Ja
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 630

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Mer

Isolerad: Nej

Rodervägen 57
891 78 Bonässund
info@processoverskott.se