

## 630 liter tank i Syrafast 316



**58 000 SEK /st exkl moms**

**Additional information:** Pharmacy; Various standard drawings are available

**Volumetric volume (L):** 630 L

**Pressure in tank:** ATM - atmosferic

**Max. temperature (°C):** 148 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 46 L

**Max Overpressure:** 3,50 Bar

**Max. working temperature:** 148 °C

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** in the bottom

**Outlet of tank:** DN40 DIN 11851

**Agitator:** yes

**Number of revolutions:** 1.385

**Power:** 0,75

**Internal diameter tank:** 1.000 mm

**Outer diameter tank:** 1.150 mm

**Cylinder height:** 780 mm

**Total height of tank:** 2.500 mm

**SKU:** 487632

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosfERIC

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 148 °C

Mobil tank: Nej

Övrig information: Pharmacy; Various standard drawings are available; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 630

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316

### Dimensioner av tank

Cylinderhöjd: 780 mm

Invändig diameter: 1.000 mm

Total höjd: 2.500 mm

Ytterdiameter: 1.150 mm

**Omrörare**

Kraft (kW): 0,75

Varvtal: 1.385

**Mer**

Isolerad: Ja