630 liter tank i Syrafast 316

32 000 SEK /st exkl moms

Additional information: The tank is mounted on a VA/Fe (galvanized) frame; handhole diameter approx. 310 mm (handhole cover plated); a flanged fitting reduces the outlet to approx. 23 mm
Volumetric volume (L): 630 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 2 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: horizontal
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: flange DN40
Internal diameter tank: 690 mm
Total height of tank: 1.900 mm

Total outer length: 2.650 mm

SKU: 738247

Mer information

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Beskrivning av produkt

Material: Syrafast 316
Modell: Horisontell
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single-skin
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: The tank is mounted on a Fe chassis (galvanized)
Omrörare: Nej
Övertryck: 2 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 630

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 690 mm
Total höjd: 1.900 mm

Mer

Isolerad: Nej

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor