

630 liter tank i Syrafast 316



50 000 SEK /st exkl moms

Additional information: chemistry; support ring and vessel flange made of mild steel; handholecover cladded

Volumetric volume (L): 630 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 300 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 15 L

Max Overpressure: 32 Bar

Max. working temperature: 300 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 316

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: flange DN50

Agitator: yes

Top: 15,80 mm

Cylinder: 7,80 mm

Bottom: 15,30 mm

Internal diameter tank: 1.000 mm

Cylinder height: 800 mm

Total height of tank: 2.000 mm

SKU: 267046

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 300 °C

Mobil tank: Nej

Övrig information: chemistry; support ring and vessel flange made of mild steel; handholecover cladded; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 630

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 800 mm

Invändig diameter: 1.000 mm

Total höjd: 2.000 mm

Tjocklek på tank

Botten: 15,30 mm

Cylinder: 7,80 mm

Topp: 15,80 mm

Mer

Värmeväxlare: RVS 316

Isolerad: Nej