

6300 liter tank i Syrafast 316



210,000,00 SEK /st exkl moms

Additional information: Manhole DN 500 (screws of the manhole cover missing); various technical documents available; ; manhole cover plated

Volumetric volume (L): 6.300 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 120 L

Max Overpressure: 16 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: flange DN80

Agitator: yes

Number of revolutions: 915

Power: 1,30

Cylinder: 7 mm

Bottom: 5,20 mm

Internal diameter tank: 2.000 mm

Cylinder height: 1.660 mm

Total height of tank: 2.900 mm

SKU: 571664

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Manhole DN 500 (screws of the manhole cover missing); various technical documents available;; manhole cover plated; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 6300

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.660 mm

Invändig diameter: 2.000 mm

Total höjd: 2.900 mm

Omrörare

Kraft (kW): 1,30

Varvtal: 915

Tjocklek på tank

Botten: 5,20 mm

Cylinder: 7 mm

Mer

Isolerad: Nej