

6300 liter tank i Syrafast 316



134 000 SEK /st exkl moms

Article type: second-hand pressure tank

Additional information: Technical drawing and KIWA documents available on demand

Volumetric volume (L): 6.300 L

Max. density P (kg/m³): 1.300

Finish stainless steel: 2b

Pressure in tank: pressure

Max. pressure (Bar): 0,20 Bar

Max. temperature (°C): 50 °C

Min. temperature (°C): -10 °C

Material wet parts: SS AISI 316L (V4A)



Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: conical 30 °

Shape of tank: cylindrical

Bottom type: dished

Total discharge: yes

Fixation points: 3 non adjustable feet

Manway(s): RVS 316

Gasket manway(s): EPDM

Fixation point(s): RVS 304

Suitable for food industry: no

Documents included: no

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 2

Position of manway: cylinder

Height manhole 1 (mm): 601 mm

Position 2nd manway: at the top

Height manhole 2 (mm): 306

Tank outlet: inside Ø 60 mm

Outlet type: DIN2605

Outlet of tank: DN50

Total outlet valve: no

Agitator: no, optional

Top: 3 mm

Cylinder: 3 mm

Bottom: 3 mm

Internal diameter tank: 2.194 mm

Distance from outlet to ground: 790 mm

Outer diameter tank: 2.200 mm



Cylinder height: 1.375 mm

Feet height: 1.323 mm

Total height of tank: 3.150 mm

Empty weight tank: 750

SKU: 707626

Mer information



Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nyttillverkad/Begagnad: Begagnad
Arbetsstryck i tank: pressure
Finish rostfritt stål: 2b
Konfiguration: single-skin
Max. arbetstemperatur: 50 °C
Maximal densitet för produkten: 1300
Min. arbetstemperatur: -10 °C
Mobil tank: Nej
Övrig information: Technical drawing available upon request
Omrörare: Nej
Övertryck: 0,20 Bar
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: dished
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316L (V4A)
Volym i liter: 6300

Utrustning

Dokument finns: Nej, det er det ikke.
Fläns för omrörare: Nej
Märkskylt: Ja
Tankutlopp: inside Ø 60 mm
Teknisk ritning finns: Ja
Utloppstyp: DIN2605
Utloppsventil: Nej

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): RVS 304



Dimensioner av tank

Cylinderhöjd: 1.375 mm
Höjd på fötter: 1.423 mm
Invändig diameter: 2.194 mm
Mått utlopp till marken: 750 mm
Total höjd: 3.250 mm
Ytterdiameter: 2.200 mm

Tjocklek på tank

Botten: 3 mm
Cylinder: 3 mm
Topp: 3 mm

Mer

Isolerad: Nej
Vikt: 750