

634 liter tank i Syrafast 316



113,000,00 kr /st exkl moms

Additional information: Pharmacy; Diameter handhole approx. 140 mm; Metallic discolouration inside

Volumetric volume (L): 634 L

Pressure in tank: pressure

Max. pressure (Bar): 2,50 Bar

Max. temperature (°C): 138 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 66 L

Max Overpressure: 2,50 Bar

Max. working temperature: 138 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: DN32 DIN 11851

Agitator: yes

Number of revolutions: 610

Power: 0,55

Internal diameter tank: 890 mm

Outer diameter tank: 1.040 mm

Total height of tank: 2.150 mm

SKU: 440453

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 138 °C

Mobil tank: Nej

Övrig information: Pharmacy; Diameter handhole approx. 140 mm; Metallic discolouration inside; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 2.50 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 634

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 890 mm

Total höjd: 2.150 mm

Ytterdiameter: 1.040 mm

Omrörare

Kraft (kW): 0,55

Varvtal: 610

Mer

Isolerad: Ja