

## 650 liter tank i Rostfritt 304



**88 000 SEK /st exkl moms**

**Additional information:** pharmacy; Metallic discoloration inside

**Volumetric volume (L):** 650 L

**Pressure in tank:** ATM - atmosferic

**Max. pressure (Bar):** 1,50 Bar

**Max. temperature (°C):** 170 °C

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** insulated

**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Max Overpressure:** 8 Bar

**Max. working temperature:** 170 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Heat exchanger:** RVS 304

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** 25

**Agitator:** yes

**Number of revolutions:** 1.415

**Power:** 1

**Cylinder:** 6 mm

**Bottom:** 5 mm

**Internal diameter tank:** 900 mm

**Outer diameter tank:** 1.040 mm

**Cylinder height:** 900 mm

**Total height of tank:** 2.380 mm

**SKU:** 271051

## Mer information

### Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 170 °C

Mobil tank: Nej

Övrig information: pharmacy; metallic discolourations inside; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 1,50 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 650

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Rostfritt 304



## Dimensioner av tank

Cylinderhöjd: 900 mm  
Invändig diameter: 900 mm  
Total höjd: 2.380 mm  
Ytterdiameter: 1.040 mm

## Omrörare

Kraft (kW): 1  
Varvtal: 1.415

## Tjocklek på tank

Botten: 5 mm  
Cylinder: 6 mm

## Mer

Värmeväxlare: RVS 304  
Isolerad: Ja