650 liter tank i Syrafast 316



70 000 SEK /st exkl moms

Additional information: pharmacy; Vessel was originally mobile on 4 plastic castors, these are no longer present; for installation, the castors would either have to be replaced on site or the feet would have to be shimmed accordingly, as the lower base/outlet extends beyond the foot end; dents at the insulation jacket; scratches inside
Volumetric volume (L): 650 L

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Pressure in tank: pressure
Max. pressure (Bar): 1,70 Bar
Min. pressure (Bar): 1,70 Bar

Max. temperature (°C): 148 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Max Overpressure: 10 Bar
Max. working temperature: 148 °C

Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: 35
Internal diameter tank: 1.000 mm
Outer diameter tank: 1.120 mm

Cylinder height: 700 mm
Total height of tank: 1.600 mm

SKU: 390230

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 148 °C
Mobil tank: Nej
Övrig information: pharmacy; The vessel was originally mobile on 4 plastic rollers, these are no longer available; For installation, the rollers would either have to be replaced on site or the feet would have to be
Övrig information2: set higher accordingly, as the lower bottom / outlet extends beyond the foot end; dents at the insulation jacket;scratches inside; we can’t give any guarantees about the heating/cooling jacket
Omrörare: Nej
Övertryck: 1.70 Bar
Total urtappning: Yes
Undertryck (vakuum): 1,70 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 650

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 700 mm
Invändig diameter: 1.000 mm
Total höjd: 1.600 mm
Ytterdiameter: 1.120 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Ja