

6500 liter tank i Syrafast 316



212,000,00 kr /st exkl moms

Additional information: Chemistry; bump at the insulation jacket; manhole cover plated

Volumetric volume (L): 6.500 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 2,60 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 180 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: DN50 DIN 11851

Agitator: yes

Number of revolutions: 15 - 61

Power: 9,20

Internal diameter tank: 2.000 mm

Outer diameter tank: 2.180 mm

Cylinder height: 1.500 mm

Total height of tank: 5.400 mm

SKU: 302112

Mer information
