

6500 liter tank i Syrafast 316



218 000 SEK /st exkl moms

Additional information: Chemistry; Slight corrosion of material in the inner tank and on the agitator shaft; bump at the insulation jacket; manhole cover plated

Volumetric volume (L): 6.500 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 2,60 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 180 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: DN50 DIN 11851

Agitator: yes

Number of revolutions: 15 - 61

Power: 9,20

Internal diameter tank: 2.000 mm

Outer diameter tank: 2.190 mm

Cylinder height: 1.500 mm

Total height of tank: 5.300 mm

SKU: 287702

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Chemistry; Slight corrosion of material in the inner tank and on the agitator shaft; bump at the insulation jacket; manhole cover plated; we can't give any guarantees about the heating/cooling

Övrig information2: jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 2,60 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 6500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.500 mm
Invändig diameter: 2.000 mm
Total höjd: 5.300 mm
Ytterdiameter: 2.190 mm

Omrörare

Kraft (kW): 9,20
Varvtal: 15 – 61

Mer

Isolerad: Ja