

## 6500 liter tank i Syrafast 316



**220,000,00 kr /st exkl moms**

**Additional information:** Chemistry; Slight corrosion of material in the inner tank and on the agitator shaft; bump at the insulation jacket; manhole cover plated

**Volumetric volume (L):** 6.500 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 2,60 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 180 L

**Max Overpressure:** 6 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 200 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** in the bottom

**Outlet of tank:** DN50 DIN 11851

**Agitator:** yes

**Number of revolutions:** 15 - 61

**Power:** 9,20

**Internal diameter tank:** 2.000 mm

**Outer diameter tank:** 2.190 mm

**Cylinder height:** 1.500 mm

**Total height of tank:** 5.300 mm

**SKU:** 287702

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Chemistry; Slight corrosion of material in the inner tank and on the agitator shaft; bump at the insulation jacket; manhole cover plated; we can't give any guarantees about the heating/cooling

Övrig information2: jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 2,60 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 6500

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316

## **Dimensioner av tank**

Cylinderhöjd: 1.500 mm  
Invändig diameter: 2.000 mm  
Total höjd: 5.300 mm  
Ytterdiameter: 2.190 mm

## **Omrörare**

Kraft (kW): 9,20  
Varvtal: 15 – 61

## **Mer**

Isolerad: Ja