

6510 liter tank i Rostfritt 304



185,000,00 kr /st exkl moms

Additional information: ethanol; a number of connections were changed by the former operator (not mentioned in the TÜV-certificates); tank on 3 support brackets made of aus Fe (not on 4 support brackets as discribed in the drawing); heating coil cylinder only in the lower cylindrical part; insulation jacket with cut-outs and dents; some residues of previous content

Volumetric volume (L): 6.510 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 2 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 165 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 34 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 165 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: flange DN65

Agitator: yes

Number of revolutions: 73

Power: 5,50

Top: 8 mm

Cylinder: 7 mm

Bottom: 7 mm

Internal diameter tank: 1.900 mm

Cylinder height: 1.800 mm

Total height of tank: 4.450 mm

SKU: 266881

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 165 °C

Mobil tank: Nej

Övrig information: ethanol; a number of connections were changed by the former operator (not mentioned in the TÜV-certificates); tank on 3 support brackets made of aus Fe (not on 4 support brackets as discribed in the

Övrig information2:

Omrörare: Ja

Övertryck: 2 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 6510



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.800 mm
Invändig diameter: 1.900 mm
Total höjd: 4.450 mm

Omrörare

Kraft (kW): 5,50
Varvtal: 73

Tjocklek på tank

Botten: 7 mm
Cylinder: 7 mm
Topp: 8 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Ja