

6570 liter tank i Rostfritt 304



185,000,00 kr /st exkl moms

Additional information: Dairy; 1 smaller dent in the insulation jacket (see photos)

Volumetric volume (L): 6.570 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 95 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 58 L

Max Overpressure: 3 Bar

Max. working temperature: 95 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: flange DN50

Agitator: yes

Number of revolutions: 18 / 36

Power: 1.2 / 2.2

Internal diameter tank: 2.180 mm

Outer diameter tank: 2.310 mm

Cylinder height: 1.400 mm

Total height of tank: 3.400 mm

SKU: 486377

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosfäric

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 95 °C

Mobil tank: Nej

Övrig information: Dairy; 1 smaller dent in the insulation jacket (see photos); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 6570

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.400 mm

Invändig diameter: 2.180 mm

Total höjd: 3.400 mm

Ytterdiameter: 2.310 mm

Omrörare

Kraft (kW): 1.2 / 2.2

Varvtal: 18 / 36

Mer

Isolerad: Ja