

660 liter tank i Syrafast 316



113 000 SEK /st exkl moms

Additional information: Pharmacy; According to the previous operator, the heating/cooling jacket of the vessel is no longer functional; further technical documents available

Volumetric volume (L): 660 L

Pressure in tank: vacuum

Max. pressure (Bar): 3,50 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 140 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: DN25 DIN 11851

Agitator: yes

Number of revolutions: 710

Power: 2,20

Top: 5 mm

Cylinder: 4 mm

Bottom: 6 mm

Internal diameter tank: 790 mm

Outer diameter tank: 940 mm

Cylinder height: 1.000 mm

Total height of tank: 3.200 mm

SKU: 293923

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated

Max. arbetstemperatur: 140 °C

Mobil tank: Nej

Övrig information: Pharmacy; According to the previous operator, the vessel's heating/cooling jacket is no longer functional; further technical documents available; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,50 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 660

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 1.000 mm
Invändig diameter: 790 mm
Total höjd: 3.200 mm
Ytterdiameter: 940 mm

Omrörare

Kraft (kW): 2,20
Varvtal: 710

Tjocklek på tank

Botten: 6 mm
Cylinder: 4 mm
Topp: 5 mm

Mer

Isolerad: Ja