660 liter tank i Syrafast 316



113 000 SEK /st exkl moms

Additional information: According to the previous operator, the heating/cooling jacket of the vessel is no longer functional; further technical documents available
Volumetric volume (L): 660 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3,50 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 140 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: DN25 DIN 11851
Agitator: yes

Number of revolutions: 710
Power: 2,20
Top: 5 mm
Cylinder: 4 mm
Bottom: 6 mm

Internal diameter tank: 790 mm
Outer diameter tank: 940 mm
Cylinder height: 1.000 mm
Total height of tank: 3.200 mm

SKU: 416624

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated
Max. arbetstemperatur: 140 °C
Mobil tank: Nej
Övrig information: Pharmacy; According to the previous operator, the vessel's heating/cooling jacket is no longer functional; further technical documents available; we can't give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3,50 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 660

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 1.000 mm
Invändig diameter: 790 mm
Total höjd: 3.200 mm
Ytterdiameter: 940 mm

Omrörare
Kraft (kW): 2,20
Varvtal: 710

Tjocklek på tank
Botten: 6 mm
Cylinder: 4 mm
Topp: 5 mm

Mer
Isolerad: Ja