665 liter tank i Syrafast 316



PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

89 000 SEK /st exkl moms

Additional information: Chemistry (caustic soda); Sight glass in the upper bottom damaged
Volumetric volume (L): 665 L
Pressure in tank: pressure
Max. temperature (°C): 80 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Total discharge: yes
Volume: 48 L
Max Overpressure: 4 Bar
Max onderdruk: 1 Bar
Max. working temperature: 80 °C

Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Outlet of tank: 54
Agitator: yes
Number of revolutions: 416
Power: 0,55

Top: 3,40 mm
Cylinder: 6 mm
Bottom: 5 mm
Internal diameter tank: 802 mm
Outer diameter tank: 940 mm

Cylinder height: 1.100 mm
Total height of tank: 2.300 mm

SKU: 479807

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 80 °C
Mobil tank: Nej
Övrig information: Chemistry (caustic soda); Sight glass in the upper bottom damaged; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 665

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material
Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 1.100 mm
Invändig diameter: 802 mm
Total höjd: 2.300 mm
Ytterdiameter: 940 mm

Omrörare
Kraft (kW): 0,55
Varvtal: 416

Tjocklek på tank
Botten: 5 mm
Cylinder: 6 mm
Topp: 3,40 mm

Mer
Isolerad: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se