

665 liter tank i Syrafast 316



88,000,00 kr /st exkl moms

Additional information: Chemistry (caustic soda); Sight glass in the upper bottom damaged

Volumetric volume (L): 665 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 80 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 48 L

Max Overpressure: 4 Bar

Max onderdruk: 1 Bar

Max. working temperature: 80 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 54

Agitator: yes

Number of revolutions: 416

Power: 0,55

Top: 3,40 mm

Cylinder: 6 mm

Bottom: 5 mm

Internal diameter tank: 802 mm

Outer diameter tank: 940 mm

Cylinder height: 1.100 mm

Total height of tank: 2.300 mm

SKU: 479807

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 80 °C

Mobil tank: Nej

Övrig information: Chemistry (caustic soda); Sight glass in the upper bottom damaged; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 665



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.100 mm
Invändig diameter: 802 mm
Total höjd: 2.300 mm
Ytterdiameter: 940 mm

Omrörare

Kraft (kW): 0,55
Varvtal: 416

Tjocklek på tank

Botten: 5 mm
Cylinder: 6 mm
Topp: 3,40 mm

Mer

Isolerad: Ja