

6700 liter tank i Rostfritt 304



70 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: Tank comes from the coffee industry, still residue from the previous product in the tank.; we can't give any guarantees about the agitator

Volumetric volume (L): 6.700 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no



Insulation: no

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 4 non adjustable feet

Manway(s): RVS 304

Gasket manway(s): unknown

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 500 mm

Tank outlet: inside Ø 50 mm

Outlet type: DIN11851

Total outlet valve: no

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Voltage: three-phase

Distance from outlet to ground: 250 mm

Outer diameter tank: 1.850 mm

Cylinder height: 2.540 mm

Total height of tank: 3.700 mm

Empty weight tank: 600

SKU: 489600

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: Tank comes from the coffee industry, still residue from the previous product in the tank.; we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 6700

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 50 mm

Teknisk ritning finns: Nej

Utloppstyp: DIN11851

Utloppsventil: Nej

Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304

Dimensioner av tank

Cylinderhöjd: 2.540 mm

Mått utlopp till marken: 250 mm

Total höjd: 3.700 mm

Ytterdiameter: 1.850 mm

Omrörare

Position motor: at the top

Typ av omrörare: propeller agitator

Spänning (Volt): three-phase

Mer

Isolerad: Nej

Vikt: 600