

## 67000 liter tank i Syrafast 316



**436 000 SEK /st exkl moms**

**Additional information:** Solvents; Manhole cylinder NW 600; total height may vary slightly (dimensions taken from drawing); some residues of previous content

**Volumetric volume (L):** 67.000 L

**Pressure in tank:** ATM - atmospheric

**Max. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 100 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** 100

**Agitator:** yes

**Top:** 6 mm

**Cylinder:** 5 mm

**Bottom:** 9 mm

**Internal diameter tank:** 3.000 mm

**Cylinder height:** 8.870 mm

**Total height of tank:** 11.500 mm

**SKU:** 475414

Mer information



## Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure

Konfiguration: single-skin

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: Solvents; Manhole cylinder NW 600; total height might deviate slightly (measures taken from drawing); some residues of previous content; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 1 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 67000

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 8.870 mm

Invändig diameter: 3.000 mm

Total höjd: 11.500 mm

**Tjocklek på tank**

Botten: 9 mm

Cylinder: 5 mm

Topp: 6 mm

**Mer**

Isolerad: Nej