67200 liter tank i Syrafast 316



438 000 SEK /st exkl moms

Additional information: Solvents; Cylinder manhole diameter: 600 mm; total height as per drawing without agitator motor
Volumetric volume (L): 67.200 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 1 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 0,25 Bar

Max. temperature (°C): 100 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: flange DN100
Agitator: yes
Number of revolutions: 76

Power: 5
Top: 8 mm
Cylinder: 6 mm
Bottom: 12 mm
Internal diameter tank: 3.000 mm

Cylinder height: 8.830 mm
Total height of tank: 11.620 mm

SKU: 476443

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single-skin
Max. arbetstemperatur: 100 °C
Mobil tank: Nej
Övrig information: Solvents; Cylinder manhole diameter: 600 mm; total height as per drawing without agitator motor; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 1 Bar
Total urtappning: Ja
Undertryck (vakuum): 0,25 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 67200

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 8.830 mm
Invändig diameter: 3.000 mm
Total höjd: 11.620 mm

Omrörare
Kraft (kW): 5
Varvtal: 76

Tjocklek på tank
Botten: 12 mm
Cylinder: 6 mm
Topp: 8 mm

Mer
Isolerad: Nej