

## 68365 liter tank i Syrafast 316



**473,000,00 SEK /st exkl moms**

**Additional information:** Maleic anhydride; some residues of previous content

**Volumetric volume (L):** 68.365 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 0,05 Bar

**Min. pressure (Bar):** 0,15 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 280 L

**Max Overpressure:** 10 Bar

**Max onderdruk:** 0,15 Bar

**Max. working temperature:** 250 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** flange DN80

**Top:** 7 mm

**Cylinder:** 7 mm

**Bottom:** 10 mm

**Internal diameter tank:** 3.000 mm

**Cylinder height:** 9.020 mm

**SKU:** 294355

Mer information

## Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Maleic anhydride; some residues of previous content; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 0,05 Bar

Total urtappning: Ja

Undertryck (vakuum): 0,15 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 68365

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 9.020 mm

Invändig diameter: 3.000 mm

**Tjocklek på tank**

Botten: 10 mm

Cylinder: 7 mm

Topp: 7 mm

**Mer**

Isolerad: Ja