6875 liter tank i Syrafast 316



219 000 SEK /st exkl moms

Additional information: Half-pipe coil only in the lower area of the cylinder; manhole diameter: 500 mm
Volumetric volume (L): 6.875 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3,20 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Volume: 120 L
Max Overpressure: 16 Bar

Max. working temperature: 200 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: cylinder
Outlet of tank: flange DN80
Agitator: yes

Number of revolutions: 950
Power: 1,30
Top: 8,30 mm
Cylinder: 7,60 mm
Bottom: 8 mm

Internal diameter tank: 1.986 mm
Cylinder height: 1.670 mm
Total height of tank: 2.710 mm
Empty weight tank: 1.600

SKU: 487992

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Half-pipe coil only in the lower part of the cylinder; manhole diameter: 500 mm; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3,20 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 6875

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 1.670 mm
Invändig diameter: 1.986 mm
Total höjd: 2.710 mm

Omrörare
Kraft (kW): 1,30
Varvtal: 950

Tjocklek på tank
Botten: 8 mm
Cylinder: 7,60 mm
Topp: 8,30 mm

Mer
Isolerad: Nej
Vikt: 1.600