

## 700 liter tank i Syrafast 316



**92 000 SEK /st exkl moms**

**Additional information:** Pharmacy; Foot frame, stainless steel; manhole diameter 410 mm; Outlet fitting incomplete

**Volumetric volume (L):** 700 L

**Pressure in tank:** pressure

**Max. pressure (Bar):** 0,30 Bar

**Max. temperature (°C):** 90 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Max Overpressure:** 3 Bar

**Max. working temperature:** 143 °C

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** in the bottom

**Outlet of tank:** DN50 DIN 11851

**Agitator:** yes

**Number of revolutions:** 127 / 261

**Power:** 0.66 / 1.3

**Internal diameter tank:** 1.050 mm

**Outer diameter tank:** 1.190 mm

**Total height of tank:** 1.600 mm

**SKU:** 300772

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 90 °C

Mobil tank: Nej

Övrig information: Pharmacy; Foot frame, stainless steel; manhole diameter 410 mm; Outlet fitting incomplete; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the

Övrig information2: agitator

Omrörare: Ja

Övertryck: 0,30 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 700

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316

### Dimensioner av tank

Invändig diameter: 1.050 mm

Total höjd: 1.600 mm

Ytterdiameter: 1.190 mm

**Omrörare**

Kraft (kW): 0.66 / 1.3

Varvtal: 127 / 261

**Mer**

Isolerad: Ja