

7000 liter tank i Syrafast 316



150,000,00 kr /st exkl moms

Article type: second-hand storage tank

Additional information: The tank comes from the fruit juice industry, there is still a brown powder on the inner wall,

Volumetric volume (L): 7.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316L (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no



Insulation: yes

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: strong conical

Total discharge: yes

Fixation points: 4 non adjustable feet

Insulation material: Rockwool

Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 316

Gasket manway(s): unknown

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 500 mm

Tank outlet: inside Ø 65 mm

Outlet type: DIN11851 male

Insulation top: yes

Insulation body: yes

Insulation bottom/sides: yes

finish of the outer jacket: welded

Insulation thickness: 50

Internal diameter tank: 1.600 mm

Distance from outlet to ground: 160 mm

Outer diameter tank: 1.700 mm

Cylinder height: 3.500 mm

Total height of tank: 4.600 mm

Empty weight tank: 1.000

SKU: 14940

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosfäric

Konfiguration: insulated

Mobil tank: Nej

Övrig information: The tank comes from the fruit juice industry, there is still a brown powder on the inner wall,

Omrörare: Nej

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: strong conical

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316L (V4A)

Volym i liter: 7000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 65 mm

Teknisk ritning finns: Nej

Utloppstyp: DIN11851 male

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): RVS 304
Isoleringsmaterial: Rockwool
Ytterbeklädnad: RVS 304

Dimensioner av tank

Cylinderhöjd: 3.500 mm
Invändig diameter: 1.600 mm
Mått utlopp till marken: 160 mm
Total höjd: 4.600 mm
Ytterdiameter: 1.700 mm

Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: welded
Isolering botten/gavlar: Ja
Isolering mantel: Ja
Isoleringsmaterial: Rockwool

Mer

Isoleringsmaterial: Ja
Isoleringstjocklek OW: 50
Isolerad: Ja
Vikt: 1.000