7000 liter tank i Rostfritt 304



119 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: we can't give any guarantees about the agitator
Volumetric volume (L): 7.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Total discharge: yes
Fixation points: 3 non adjustable feet

Insulation material: Rockwool
Outer jacket (ornamental wall): RVS 304
Manway(s): RVS 304
Gasket manway(s): unknown
Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)
Suitable for food industry: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: no

Flange for agitator: no
Number of manways: 1
Position of manway: at the top
Height manhole 1 (mm): 410 mm
Tank outlet: inside Ø 50 mm

Outlet type: DIN11851
Outlet of tank: DN50
Total outlet valve: yes
Agitator: yes
Agitator type: propeller agitator

Position engine: at the top
Number of revolutions: 450
Power: 1,50
Voltage: 400 V - three-phase
Current: 5,50

Top: 4 mm
Insulation body: yes
Insulation bottom/sides: yes
finish of the outer jacket: welded

Insulation thickness: 50

Internal diameter tank: 1.742 mm
Distance from outlet to ground: 400 mm
Outer diameter tank: 1.800 mm
Cylinder height: 3.500 mm
Feet height: 980 mm

Total height of tank: 5.740 mm
Empty weight tank: 850

SKU: 489429

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: insulated
Mobil tank: Nej
Övrig information: we can’t give any guarantees about the agitator
Omrörare: Ja
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: conical
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 7000

Utrustning
Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Nej
Utloppstyp: DIN11851
Utloppsventil: Ja

Översikt material
Material: Rostfritt 304
Fixeringspunkt(er): RVS 304
Isoleringsmaterial: Rockwool
Material vätskeberörd del på omrörare: SS AISI 304 (V2A)
Ytterbeklädnad: RVS 304

Dimensioner av tank
Cylinderhöjd: 3.500 mm
Höjd på fötter: 980 mm
Invändig diameter: 1.742 mm
Mått utlopp till marken: 400 mm
Total höjd: 5.700 mm
Ytterdiameter: 1.800 mm

Omrörare
Kraft (kW): 1,50
Position motor: at the top
Typ av omrörare: propeller agitator
Varvtal: 450
Spänning (Volt): three-phase

Tjocklek på tank
Topp: 4 mm

Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: welded
Isolering botten/gavlar: Ja
Isolering mantel: Ja
Isoleringsmaterial: Rockwool

Mer

Isoleringstjocklek OW: 50
Isolerad: Ja
Vikt: 800