

7000 liter tank i Rostfritt 304



118,000,00 kr /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the agitator

Volumetric volume (L): 7.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes



Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 3 non adjustable feet

Insulation material: Rockwool

Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 304

Gasket manway(s): unknown

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Total outlet valve: yes

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Voltage: three-phase

Insulation body: yes

Insulation bottom/sides: yes

finish of the outer jacket: welded

Insulation thickness: 50

Outer diameter tank: 1.800 mm

Cylinder height: 3.500 mm

Empty weight tank: 800

SKU: 489429

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 7000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Livsmedelsklassad: Ja

Teknisk ritning finns: Nej

Utloppsventil: Ja

Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304

Isoleringsmaterial: Rockwool

Ytterbeklädnad: RVS 304

Dimensioner av tank

Cylinderhöjd: 3.500 mm

Ytterdiameter: 1.800 mm

Omrörare

Position motor: at the top

Typ av omrörare: propeller agitator

Spänning (Volt): three-phase

Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: welded

Isolering botten/gavlar: Ja

Isolering mantel: Ja

Isoleringsmaterial: Rockwool

Mer

Isoleringstjocklek OW: 50

Isolerad: Ja

Vikt: 800