70000 liter tank i Rostfritt 304



PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

723 000 SEK /st exkl moms

Additional information: Manhole in cylinder diameter 600 mm; slight dents in cylinder interior; some residues of previous content
Volumetric volume (L): 70.000 L
Pressure in tank: pressure
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: no

Max Overpressure: 6 Bar
Max. working temperature: 120 °C
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Agitator: yes
Number of revolutions: 23
Power: 22

Top: 5 mm
Cylinder: 5 mm
Bottom: 6 mm
Internal diameter tank: 3.490 mm
Cylinder height: 8.250 mm

Total height of tank: 11.040 mm
Total outer width: 3.820 mm
Total outer length: 3.820 mm

SKU: 423590

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single jacketed with heat-exchanger
Mobil tank: Nej
Övrig information: manhole in the cylinder diameter 600 mm; Complete manufacturer documentation available; A ladder also available upon request; tank has fixtures for field installation of insulation (this fixture is
Övrig information2: slightly dented); some residues of previous content; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Nej
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 70000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material
Material: Rostfritt 304

Dimensioner av tank
Cylinderhöjd: 8.250 mm
Invändig diameter: 3.490 mm
Total höjd: 11.040 mm

Omrörare
Kraft (kW): 22
Varvtal: 23

Tjocklek på tank
Botten: 6 mm
Cylinder: 5 mm
Topp: 5 mm

Mer
Isolerad: Nej