

7040 liter tank i Syrafast 316



272 000 SEK /st exkl moms

Additional information: Saline solution; Slight metallic discoloration inside; The production and documentation drawings are available from the manufacturer and can be purchased separately from there; some residues of previous content; bump at the insulation jacket; pipe end cut flush

Volumetric volume (L): 7.040 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 2,50 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 140 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 176 L

Max Overpressure: 2 Bar

Max onderdruk: 1 Bar

Max. working temperature: 140 °C

Type HE on the bottom: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 38

Internal diameter tank: 1.880 mm

Outer diameter tank: 2.100 mm

Cylinder height: 2.000 mm

Total height of tank: 3.700 mm

Empty weight tank: 1.120

SKU: 278860

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 140 °C

Mobil tank: Nej

Övrig information: Saline solution; Slight metallic discoloration inside; The production and documentation drawings are available from the manufacturer and can be purchased separately from there; some residues of

Övrig information2: previous content;bump at the insulation jacket;pipe end cut flush; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 2,50 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 7040

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 2.000 mm
Invändig diameter: 1.880 mm
Total höjd: 3.700 mm
Ytterdiameter: 2.100 mm

Mer

Isolerad: Ja
Vikt: 1.120