72 liter tank i Syrafast 316



94 000 SEK /st exkl moms

Additional information: Tank lid made of 1.4404 (stainless steel 316)
Volumetric volume (L): 72 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 2,50 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: no
Volume: 4 L
Max Overpressure: 4 Bar

Max onderdruk: 1 Bar
Max. working temperature: 150 °C
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Agitator: yes
Number of revolutions: 705
Power: 1,50

Internal diameter tank: 340 mm
Outer diameter tank: 370 mm
Cylinder height: 720 mm
Total height of tank: 1.600 mm

SKU: 568370

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 150 °C
Mobil tank: Nej
Övrig information: Pharmacy; Tank lid made of 1.4404 (stainless steel 316); we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 2,50 Bar
Total urtappning: Nej
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 72

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 720 mm
Invändig diameter: 340 mm
Total höjd: 1.600 mm
Ytterdiameter: 370 mm

Omrörare
Kraft (kW): 1,50
Varvtal: 705

Mer
Isolerad: Nej