

7250 liter tank i Syrafast 316



88,000,00 kr /st exkl moms

Additional information: chemistry; tank mounting: traverse Fe; outlet fitting incomplete; manhole cover is missing

Volumetric volume (L): 7.250 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Max Overpressure: 5 Bar

Max. working temperature: 160 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: flange DN80

Agitator: yes

Number of revolutions: 125

Power: 4

Top: 4 mm

Cylinder: 5 mm

Bottom: 5 mm

Internal diameter tank: 2.000 mm

Cylinder height: 2.000 mm

Total height of tank: 3.700 mm

SKU: 270514

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosfERIC

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: chemistry; tank mounting: traverse Fe; outlet fitting incomplete; manhole cover is missing; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 7250

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 2.000 mm
Invändig diameter: 2.000 mm
Total höjd: 3.700 mm

Omrörare

Kraft (kW): 4
Varvtal: 125

Tjocklek på tank

Botten: 5 mm
Cylinder: 5 mm
Topp: 4 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Nej