

729 liter tank i Syrafast 316



179,000,00 kr /st exkl moms

Additional information: Tank is currently on a pedestal; should this be used for installation, the total height would increase to approx. 2,600 mm

Volumetric volume (L): 729 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 73 L

Max Overpressure: 3 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: available

Agitator: yes

Number of revolutions: 150

Power: 1,10

Top: 6,40 mm

Cylinder: 7 mm

Bottom: 4,80 mm

Internal diameter tank: 988 mm

Outer diameter tank: 1.150 mm

Cylinder height: 650 mm

Total height of tank: 2.470 mm

Empty weight tank: 750

SKU: 285337

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Tank is currently on a pedestal; should this be used for installation, the total height would increase to approx. 2,600 mm; we can't give any guarantees about the heating/cooling jacket; we can't

Övrig information2: give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 729

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 650 mm

Invändig diameter: 988 mm

Total höjd: 2.470 mm

Ytterdiameter: 1.150 mm

Omrörare

Kraft (kW): 1,10

Varvtal: 150

Tjocklek på tank

Botten: 4,80 mm

Cylinder: 7 mm

Topp: 6,40 mm

Mer

Isolerad: Ja

Vikt: 750