733 liter tank i Syrafast 316



185 000 SEK /st exkl moms

Additional information: Device for holding load cells under the feet (the load cells themselves are no longer present)
Volumetric volume (L): 733 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 6 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 55 L
Max Overpressure: 6 Bar

Max onderdruk: 1 Bar
Max. working temperature: 150 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: 25
Agitator: yes

Number of revolutions: 910
Power: 1,50
Internal diameter tank: 880 mm
Outer diameter tank: 1.030 mm
Total height of tank: 2.250 mm

SKU: 489982

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 150 °C
Mobil tank: Nej
Övrig information: Pharmacy; Device for holding load cells under the feet (the load cells themselves are no longer present); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees
Övrig information2: about the agitator
Omrörare: Ja
Övertryck: 6 Bar
Total urtappning: Yes
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 733

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Invändig diameter: 880 mm
Total höjd: 2.250 mm
Ytterdiameter: 1.030 mm

Omrörare
Kraft (kW): 1,50
Varvtal: 910

Mer
Isolerad: Ja