

736 liter tank i Syrafast 316



70,000,00 kr /st exkl moms

Additional information: Pharmaceutical Chemistry; 3 support brackets, st. st.; Half-coil, Aisi 304 around the lower cylinder area and the lower bottom; hand hole DN 200 (hand hole cover is missing); Insulating jacket made of material 1.0425; some residues of previous content

Volumetric volume (L): 736 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 20 L

Max Overpressure: 16 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: available

Top: 2,60 mm

Cylinder: 4 mm

Bottom: 2,30 mm

Internal diameter tank: 800 mm

Outer diameter tank: 1.050 mm

Cylinder height: 1.250 mm

Total height of tank: 2.200 mm

SKU: 289979

Mer information
