736 liter tank i Syrafast 316



70 000 SEK /st exkl moms

Additional information: Pharmaceutical Chemistry; 3 support brackets, st. st.; Half-coil, Aisi 304 around the lower cylinder area and the lower bottom; hand hole DN 200 (hand hole cover is missing); Insulating jacket made of material 1.0425; some residues of previous content
Volumetric volume (L): 736 L
Pressure in tank: pressure and vacuum

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. pressure (Bar): 3,20 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 20 L
Max Overpressure: 16 Bar

Max onderdruk: 1 Bar
Max. working temperature: 200 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: available
Top: 2,60 mm

Cylinder: 4 mm
Bottom: 2,30 mm
Internal diameter tank: 800 mm
Outer diameter tank: 1.050 mm
Cylinder height: 1.250 mm

Total height of tank: 2.200 mm

SKU: 413501

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Pharmaceutical Chemistry; 3 support brackets, st. st.; Half-coil, Aisi 304 around the lower cylinder area and the lower bottom; hand hole DN 200 (hand hole cover is missing); Insulating jacket made
Övrig information2: of material 1.0425 ; some residues of previous content; we can’t give any guarantees about the heating/cooling jacket
Omrörare: Nej
Övertryck: 3,20 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 736

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material
Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 1.250 mm
Invändig diameter: 800 mm
Total höjd: 2.200 mm
Ytterdiameter: 1.050 mm

Tjocklek på tank
Botten: 2,30 mm
Cylinder: 4 mm
Topp: 2,60 mm

Mer
Isolerad: Ja