

740 liter tank i Syrafast 316



80,000,00 kr /st exkl moms

Additional information: Pharmacy; Chassis, Fe (painted); diameter of hand hole approx. 305 mm; total length specified with drawbar folded up (as in photos)

Volumetric volume (L): 740 L

Pressure in tank: ATM - atmospheric

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: horizontal

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: no

Volume: 25 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: flange DN40

Number of revolutions: 940

Power: 0,95

Cylinder: 4 mm

Bottom: 5 mm

Internal diameter tank: 770 mm

Total height of tank: 2.300 mm

Total outer length: 2.450 mm

SKU: 478872

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Horisontell

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmacy; Chassis, Fe (painted); diameter of hand hole approx. 305 mm; total length specified with drawbar folded up (as in photos)

Omrörare: Nej

Övertryck: 6 Bar

Total urtappning: Nej

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 740

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Invändig diameter: 770 mm

Total höjd: 2.300 mm

Omrörare

Kraft (kW): 0,95

Varvtal: 940

Tjocklek på tank

Botten: 5 mm

Cylinder: 4 mm

Mer

Isolerad: Nej