

742 liter tank i Syrafast 316



61 000 SEK /st exkl moms

Additional information: Pharmaceutical Chemistry; 1 manhole DN 400 in the cylinder, 1 hand hole DN 200 in the upper bottom (sight glass in the hand hole cover is missing)

Volumetric volume (L): 742 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: flange DN80

Cylinder: 5 mm

Bottom: 6 mm

Internal diameter tank: 800 mm

Cylinder height: 1.240 mm

Total height of tank: 2.350 mm

SKU: 284605

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single-skin

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: Pharmaceutical Chemistry; 1 manhole DN 400 in the cylinder, 1 hand hole DN 200 in the upper bottom (sight glass in the hand hole cover is missing)

Omrörare: Nej

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 742

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.240 mm

Invändig diameter: 800 mm

Total höjd: 2.350 mm

Tjocklek på tank

Botten: 6 mm

Cylinder: 5 mm

Mer

Isolerad: Nej