

75 liter tank i Syrafast 316



461 000 SEK /st exkl moms

Additional information: Outlet: Gemü Bottom-Seat Valve with Sampling Port

Volumetric volume (L): 75 L

Pressure in tank: vacuum

Min. pressure (Bar): 1 Bar



Max. temperature (°C): 140 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 6 L

Max Overpressure: 13,20 Bar

Max onderdruk: 1 Bar

Max. working temperature: 140 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: available

Agitator: yes

Number of revolutions: 112 - 575

Power: 0,18

Internal diameter tank: 400 mm

Cylinder height: 450 mm

Total height of tank: 1.531 mm

Total outer width: 903 mm

Total outer length: 1.015 mm

SKU: 705466



Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: vacuum

Konfiguration: insulated

Max. arbetstemperatur: 140 °C

Mobil tank: Nej

Övrig information: Outlet: Gemü Bottom-Seat Valve with Sampling Port; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 75

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 450 mm

Invändig diameter: 400 mm

Total höjd: 1.531 mm



Omrörare

Kraft (kW): 0,18

Varvtal: 112 – 575

Mer

Isolerad: Ja