

7500 liter tank i Rostfritt 304



217 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Volumetric volume (L): 7.500 L

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: no

Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Total discharge: yes
Fixation points: 4 adjustable feet

Type of HE on the cylinder: heating/cooling jacket
Position HE: the middle part of the cilinder
Outer jacket (ornamental wall): RVS 304
Manway(s): RVS 304
Gasket manway(s): unknown

Fixation point(s): RVS 304
Wet parts agitator(s): SS AISI 304 (V2A)
Suitable for food industry: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: no
Flange for agitator: no
Position of manway: at the top
Hinged lid: yes
Tank outlet: inside Ø 76 mm

Agitator: yes
Agitator type: tripod
Position engine: at the top
Number of revolutions: 700
Power: 2,20

Current: 6/6.8

Outer diameter tank: 2.300 mm

Total height of tank: 3.700 mm

SKU: 288002

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 7500



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 76 mm
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304
Material vätskeberörd del på omrörare: SS AISI 304 (V2A)
Ytterbeklädnad: RVS 304

Dimensioner av tank

Total höjd: 3.700 mm
Ytterdiameter: 2.300 mm

Värmeväxlare

Position värmeväxlare: the middle part of the cilinder
Typ av värmeväxlare på cylinder: heating/cooling jacket

Omrörare

Kraft (kW): 2,20
Position motor: at the top
Typ av omrörare: tripod
Varvtal: 700

Mer

Isolerad: Ja