7500 liter tank i Syrafast 316



89 000 SEK /st exkl moms

Additional information: 2 stainless steel bearing shells; 1 manhole diameter approx. 600 mm in the front base; 1 manhole approx. 400 mm on the vessel; double jacket only around the lower cylinder area (upper heating connections cut off); connection in the manhole cover of the front base was probably used as an outlet by the previous operator; some residues of previous content
Volumetric volume (L): 7.500 L

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Pressure in tank: ATM - atmosferic
Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)

Model: horizontal
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Total discharge: yes
Volume: 240 L
Max Overpressure: 2,50 Bar
Max onderdruk: 1 Bar
Max. working temperature: 150 °C

Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Outlet of tank: 55
Internal diameter tank: 1.980 mm
Outer diameter tank: 2.080 mm
Total height of tank: 2.550 mm
Total outer length: 3.200 mm

SKU: 571820

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Horisontell
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 150 °C
Mobil tank: Nej
Övrig information: 2 stainless steel bearing shells; 1 manhole diameter approx. 600 mm in the front base; 1 manhole approx. 400 mm on the vessel; double jacket only around the lower cylinder area (upper heating
Övrig information2: connections cut off); connection in the manhole cover of the front base was probably used as an outlet by the previous operator; some residues of previous content
Omrörare: Nej
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 7500

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 1.980 mm
Total höjd: 2.550 mm
Ytterdiameter: 2.080 mm

Mer
Isolerad: Nej